

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

Efficient Parity Operations

Inventor(s):
Michael B. Jacobson

ATTORNEY'S DOCKET NO. 10971442-1

1 **TECHNICAL FIELD**

2 This invention relates to parity operations in redundant disk drive systems,
3 and particularly to parity operations in such systems that utilize two or more parity
4 segments per storage stripe.

5
6 **BACKGROUND OF THE INVENTION**

7 *Sub* Modern, high-capacity data storage systems often utilize a plurality of
8 physical disk drives for redundant storage of data. This arrangements speeds data
9 access as well as protecting against data loss that might result from the failure of
10 any single disk.

11 There are two common methods of storing redundant data. According to
12 the first or "mirror" method, data is duplicated and stored on two separate areas of
13 the storage system. In a disk array, for example, identical data is stored on two
14 separate disks. This method has the advantages of high performance and high data
15 availability. However, the mirror method is also relatively expensive, effectively
16 doubling the cost of storing data.

17 In the second or "parity" method, a portion of the storage area is used to
18 store redundant data, but the size of the redundant storage area is less than the
19 remaining storage space used to store the original data. For example, in a disk
20 array having six disks, five disks might be used to store data, with the sixth disk
21 being dedicated to storing redundant data, which is referred to as "parity" data.
22 The parity data allows reconstruction of the data from one data disk, using the
23 parity data in conjunction with the data from surviving disks. The parity method is
24 advantageous because it is less costly than the mirror method, but it also has lower
25 performance and availability characteristics in comparison to the mirror method.

1 One aspect of this invention involves storing redundant data according to
2 parity techniques. In conventional disk arrays utilizing parity storage, the space on
3 the storage disks are configured into multiple storage stripes, where each storage
4 stripe extends across the storage disks. Each stripe consists of multiple segments
5 of storage space, where each segment is that portion of the stripe that resides on a
6 single storage disk of the disk array.

7 Fig. 1 illustrates a conventional disk array 12 having six storage disks 13.
8 In this simplified example, there are five storage stripes extending across the
9 storage disks. Fig. 1 highlights data and storage segments of a single one of these
10 five stripes. *Data* segments of the indicated stripe are indicated by cross-hatching.
11 The corresponding *parity* segment of this same stripe is illustrated in solid black.
12 Generally, of the six segments comprising any given stripe, five of the segments
13 are data segments and the sixth segment is a parity segment.

14 This type of parity storage is referred to as 5 + 1 parity storage, indicating
15 that there are five data segments for every single parity segment. This scheme is
16 more generally referred to as N + 1 grouping, where N is the actual number of data
17 segments in a data stripe.

18 N + 1 redundancy grouping such as illustrated in Fig. 1 protects against the
19 loss of any single physical storage device. If the storage device fails, its data can
20 be reconstructed from the surviving data. The calculations performed to recover
21 the data are straightforward, and are well-known. Generally, a single parity
22 segment P is calculated from data segments D₀ through D_{N-1} in accordance with
23 the following equation:

$$24 \quad P = x_0 + x_1 + x_2 + x_{N-1}$$

25

1 where x_0 through x_{N-1} correspond to the data from data segments D_0 through D_{N-1} .

2 After the loss of any single data segment, its data can be recovered through a
3 straightforward variation of the same equation.

4 In many systems, however, it is becoming important to protect against the
5 loss of more than a single storage device. Thus, it is becoming necessary to
6 implement $N + 2$ grouping in redundant storage systems.

7 While $N + 2$ redundancy grouping enhances data protection, it also involves
8 more complex calculations—both in initially calculating parity segments and in
9 reconstructing any lost data segments.

10 A general form of the $N + 2$ parity computation is as follows:

$$11 \quad P = p_0x_0 + p_1x_1 + p_2x_2 + p_{N-1}x_{N-1}$$

$$12 \quad Q = q_0x_0 + q_1x_1 + q_2x_2 + q_{N-1}x_{N-1}$$

13 where:

14 P is the value of a first parity segment;

15 Q is the value of a second parity segment;

16 x_0 through x_{N-1} are the values of the data segments

17 p_0 through p_{N-1} and q_0 through q_{N-1} are constant coefficients that are
18 particular to a given parity scheme.

19 These equations form a two-equation system that, by the rules of linear
20 algebra, can potentially solve for any two unknowns x_a through x_b which represent
21 the data from a single stripe of any two failed storage devices. One requirement is
22 that the two sets of coefficients p_i and q_i be linearly independent. This
23 requirement is met, for example, if $p_0 = 1, p_1 = 1, p_2 = 1$; etc.; and $q_0 = 1, q_1 = 2, q_2$
24 $= 3$; etc. Other examples are also possible.

1 The mathematics of $N + 2$ parity are well-known and are not the primary
2 subject of this description. However, it is apparent from the brief description
3 given above that $N + 2$ parity computations are significantly more complex than N
4 $+ 1$ parity computations. In actual implementations of $N + 2$ disk arrays, this
5 complexity threatens to limit the data throughput of storage device controllers and,
6 consequently, of the overall disk array.

7 This invention includes methods and means for maintaining adequate data
8 throughput in spite of the added complexity resulting from $N + 2$ parity
9 calculations.

10 11 **SUMMARY**

12 In accordance with one aspect of the invention, every possible parity-
13 related computation is identified as a different scenario. A coefficient subset is
14 selected or computed for each different scenario and stored in a memory table
15 during an initialization process. To perform a particular operation, its scenario is
16 identified and the corresponding coefficient subset is located. Hardware logic is
17 then instructed to perform the actual parity operation, using the identified
18 coefficient subset. This allows very efficient computations, using coefficients that
19 are computed and selected ahead of time.

20 21 **BRIEF DESCRIPTION OF THE DRAWINGS**

22 Fig. 1 is a block diagram showing $N+1$ redundancy grouping in accordance
23 with the prior art.

24 Fig. 2 is a block diagram showing $N+2$ redundancy grouping as used in the
25 described embodiment of the invention.

1 Fig. 3 is a block diagram illustrating layout of a memory table in
2 accordance with the invention.

3 Fig. 4 is a flowchart illustrating preferred steps in accordance with the
4 invention.

5 Fig. 5 is a block diagram showing pertinent components of a disk controller
6 in accordance with the invention.

7 8 **DETAILED DESCRIPTION**

9 **Parity Operations**

10 Referring to Fig. 2, a redundant data storage system 20 in accordance with
11 the invention utilizes storage disks 22 with data stripes 24. Each data stripe 24
12 comprises a plurality of data segments x_0 through x_{N-1} and at least two
13 corresponding parity segments P and Q. P and Q are derived from the data
14 segments x_0 through x_{N-1} , from a first set of parity coefficients p_0 through p_{N-1} , and
15 from a second set of parity coefficients q_0 through q_{N-1} . The parity coefficients
16 correspond to respective data segments in accordance with the equations below:

$$17 \quad P = p_0x_0 + p_1x_1 + p_2x_2 + p_{N-1}x_{N-1}$$

$$18 \quad Q = q_0x_0 + q_1x_1 + q_2x_2 + q_{N-1}x_{N-1}$$

19 In accordance with the invention, parity operations are generally classified
20 as parity segment generation operations, parity segment regeneration operations,
21 and data segment reconstruction operations.

22 A parity segment *generation* operation is performed when creating a new
23 data stripe—the parity segments are created based on completely new data.

24 A parity segment *regeneration* operation is performed with respect to an
25 existing stripe, either when new data causes the addition of a new data segment or

when a read/modify/write cycle modifies one or more data segments. In a parity segment regeneration operation, the parity segments are modified incrementally, without reading an entire data stripe. For example, suppose that new data causes the addition of a new data segment x_4 . P_{NEW} is calculated as follows:

$$P_{NEW} = P_{OLD} + p_4 x_4$$

Similarly, suppose that data segment x_2 is modified as the result of a read/modify/write cycle. In this case, P_{NEW} is calculated as follows:

$$P_{NEW} = P_{OLD} - p_2 x_{2OLD} + p_2 x_{2NEW}$$

Calculating new P and Q values from the old data segment values involves significantly fewer memory reads than calculating P and Q from scratch after every stripe modification.

In accordance with the invention, parity segment regeneration operations are further classified as either parity regenerations resulting from added data segments or parity regenerations resulting from a modified data segment.

Data segment *reconstruction* operations include two sub-classifications: single data segment reconstruction operations and double data segment reconstruction operations. A single data segment can be reconstructed from either the P or the Q parity segment in combination with the surviving data segments. Generally, a data segment x_a is reconstructed from either parity segment P or Q as follows:

$$x_a = f(p_0, p_a)x_0 + f(p_1, p_a)x_1 + \dots + f(p_a)P + \dots + f(p_{N-1}, p_a)x_{N-1}$$

$$x_a = f(q_0, q_a)x_0 + f(q_1, q_a)x_1 + \dots + f(q_a)Q + \dots + f(q_{N-1}, q_a)x_{N-1}$$

where $f()$ is a transformation function that generates an appropriate coefficient particular to the parity generation code being used.

One implementation of these equations is as follows:

$$x_a = p_a^{-1}(p_0x_0 + p_1x_1 + \dots + P + \dots + p_{N-1}x_{N-1})$$

$$x_a = p_a^{-1}(q_0x_0 + q_1x_1 + \dots + Q + \dots + q_{N-1}x_{N-1})$$

Two data segments can be reconstructed from the P and the Q parity segments in combination with the surviving data segments. Generally, two data segments x_a and x_b are reconstructed from parity segments P and Q as follows:

$$x_a = f(p_0, q_0, p_a, p_b, q_a, q_b)x_0 + f(p_1, q_1, p_a, p_b, q_a, q_b)x_1 + \dots + f(p_a, p_b, q_a, q_b)P + f(p_k, q_k, p_a, p_b, q_a, q_b)x_k + f(p_{k+1}, q_{k+1}, p_a, p_b, q_a, q_b)x_{k+1} + \dots + f(p_a, p_b, q_a, q_b)Q + \dots + f(p_{N-1}, q_{N-1}, p_a, p_b, q_a, q_b)x_{N-1}$$

$$x_b = f(p_0, q_0, p_a, p_b, q_a, q_b)x_0 + f(p_1, q_1, p_a, p_b, q_a, q_b)x_1 + f(p_a, p_b, q_a, q_b)P + f(p_k, q_k, p_a, p_b, q_a, q_b)x_k + f(p_{k+1}, q_{k+1}, p_a, p_b, q_a, q_b)x_{k+1} + \dots + f(p_a, p_b, q_a, q_b)Q + \dots + f(p_{N-1}, q_{N-1}, p_a, p_b, q_a, q_b)x_{N-1}$$

where $f()$, again, is a transformation function that generates an appropriate coefficient particular to the parity generation code being used.

One implementation of these equations is as follows:

$$x_a = (p_a, q_b + p_b q_a)^{-1} ((q_b p_0 + p_b q_0)x_0 + (q_b p_1 + p_b q_1)x_1 + \dots + q_b P + \dots + (q_b p_k + p_b q_k)x_k + (q_b p_{k+1} + p_b q_{k+1})x_{k+1} + \dots + p_b Q + \dots + (q_b p_{N-1} + p_b q_{N-1})x_{N-1})$$

$$x_b = (p_a q_b + p_b q_a)^{-1} ((q_a p_0 + p_a q_0)x_0 + (q_a p_1 + p_a q_1)x_1 + \dots + q_a P + \dots + (q_a p_k + p_a q_k)x_k + (q_a p_{k+1} + p_a q_{k+1})x_{k+1} + \dots + p_a Q + \dots + (q_a p_{N-1} + p_a q_{N-1})x_{N-1})$$

Generally, all of the parity operations described above can be accomplished by using a different combination of known coefficients chosen from a base set having a finite number of such coefficients. These coefficients include p_0 - p_{N-1} , q_0 - q_{N-1} , and the coefficients resulting from the transform functions $f()$. Any particular parity operation utilizes a subset of these coefficients, depending on the

Sub a2
1 actual data or parity segment being calculated. The particular subset of
2 coefficients needed for a particular calculation depends on both the classification
3 of the operation and upon the specific data and/or parity segments involved. Thus,
4 within a given classification of parity operation, there are different situations or
5 *scenarios*, each of which calls for a different subset of coefficients. For example,
6 one scenario occurs when adding data segment x_5 to a stripe, when coefficients p_5
7 and q_5 are needed. Another scenario occurs when adding data segment x_6 to a
8 stripe, when coefficients p_6 and q_6 are needed.

10 Coefficient Subsets

Sub a3
11 Fig. 3 shows a memory array 30 that contains plurality of coefficient
12 subsets 31. Each coefficient subset is a list or concatenation of pre-selected and/or
13 pre-computed coefficients that are applied to corresponding segments of data to
14 produce a parity computation result. In accordance with the invention, a different
15 subset of coefficients is pre-selected and stored for each different operation
16 scenario. The subsets are then formatted and packed in a linear memory array for
17 reference and direct use by parity operation logic. Because different scenarios call
18 for different numbers of coefficients, the subsets are not of the same length or size.

19 Each coefficient is a single byte in the described embodiment of the
20 invention. The term "packed" means that the subsets or strings of coefficients are
21 concatenated in linear memory, preferably with no intervening unused spaces, to
22 conserve storage space.

23 There is a one-to-one correspondence between a coefficient in a subset and
24 a segment of data (either a data segment or a parity segment) when performing the
25

1 parity operation. Each coefficient is applied only to its corresponding data
2 segment or parity segment to produce the result of the operation.

3 One coefficient subset is included in the array for each possible parity
4 computation case or scenario. Unique indexing formulas are used to locate the
5 beginning of a subset in the array for each specific computational scenario.
6 Generally, the subsets are arranged in pairs, corresponding to computations
7 involving P and Q, respectively.

8 Referring to Fig. 3, memory array 30 includes a plurality of classification
9 groups 32, 33, 34, 35, and 36, each of which contains the coefficient subsets 31
10 corresponding to a particular parity operation classification. Each subset in a
11 classification group has coefficients for a specific scenario that occurs within the
12 group's classification. With one exception, the coefficient subsets are the same
13 size within any given classification group.

14 Within array 30, particular classification groups are located by computing a
15 group offset from the beginning of the array to the beginning of the group. This
16 group offset is the base index into the array for the group. To locate a specific
17 coefficient subset within a classification group, a subset offset from the beginning
18 of the group is added to the base index. This produces an index into the array that
19 locates the beginning of the desired coefficient subset.

20 In accordance with one embodiment of the invention, the general parity
21 operation classifications are defined as follows:

- 22 1. **Parity Generation Operations**—Partial or full new stripe that has
23 no pre-existing data or parity.
24
25

- 1 2. **Parity Regeneration Operations Resulting From Added**
2 **Segments**—Incremental growth of a stripe by incorporating new
3 data segments into the two parity segments.
- 4 3. **Parity Regeneration Operations Resulting From Segment**
5 **Modification**—Modification of a data segment that is already
6 incorporated in the two parity segments (read/modify/write).
- 7 4. **Single Data Segment Reconstruction**—Reconstruction of a single
8 data segment using one of the parity segments and the surviving data
9 segments from the strip. Reconstruction from either P or Q parity
10 segments is supported because in the case of two failed storage
11 devices, one of the failed storage devices may hold P or Q.
- 12 5. **Double Data Segment Reconstruction**—Reconstruction of two
13 data segments of a stripe using the two parity segments P and Q, and
14 the surviving data segments from the stripe.

15
16 **Structure of Classification 1 Coefficient Subsets**

17 The first classification group 32 of the array contains the coefficient subsets
18 for parity generation operations. A parity generation operation generates new P
19 and Q segments from new data segments x_0 through x_{N-1} . There are only two
20 coefficient subsets in this classification group. The subsets correspond
21 respectively to the generation of parity segments P and Q:

22 P: $\{p_0, p_1, \dots, p_{N-1}\}$ and

23 Q: $\{q_0, q_1, \dots, q_{N-1}\}$

24 Each of these subsets is the same length (N).
25

Structure of Classification 2 Coefficient Subsets

The second classification group 33 of the array contains the coefficient subsets for parity operations that add incrementally to a stripe. This type of operation updates P and Q segments in combination with any given contiguous range of new or added data segments x_a through x_b (where $b < N$ and $a \leq b$). There are multiple different scenarios of these operations, corresponding to every possible range a through b of data segments within data segments 0 through $N-1$. Each scenario calls for a different subset of coefficients. For example, if the new or added data segments are x_3 and x_4 , the required coefficient subset to calculate P is $\{p_3, p_4\}$. If the new or added data segments are x_2 through x_5 , the required coefficient subset to calculate P is $\{p_2, p_3, p_4, p_5\}$. The total of possible ranges within data segments 0 through $N-1$ depends on the value of N .

Each coefficient subset of classification group 2 contains two initial parameters that indicate whether the subset applies to calculations of P or to calculations of Q. Each of these initial parameters is set to either "0" or "1". A value of "1" for the first of these coefficients indicates that the calculation involves parity segment P. A value of "1" for the second of these coefficients indicates that the calculation involves parity segment Q. Only one of these two parameters should be set equal to "1" at any given time.

The remaining coefficients in a Classification 2 subset are the sub-range of coefficients that are used to regenerate P and Q from newly added data stripes. Thus, the classification group contains a plurality of coefficient subsets of the form:

P: $\{1, 0, p_a, \dots, p_b\}$ and

Q: $\{0, 1, q_a, \dots, q_b\}$

Classification group 33 includes a plurality of subsets such as these, depending on N , corresponding to every range of a through b , within the larger range of 0 through $N-1$. The coefficient subsets in this section of the array have varying lengths or sizes, equal to $b - a$ for each operation scenario.

Within this classification group, coefficient subsets are arranged and grouped by length. That is, the coefficient subsets containing the smallest number of coefficients are placed in the initial part of the classification group. The coefficient subsets containing the largest number of coefficients are placed at the end of the classification group. Within each of these groupings, the coefficient subsets are arranged in order according to the lower coefficient subscript of the range that is covered by the coefficient subset. Thus, the subsets having $a = 0$ are positioned first, the subsets having $a = 1$ next, and so on.

Structure of Classification 3 Coefficient Subsets

The coefficient subsets in the third classification group 34 are used to update P and Q when a single data segment is modified. This type of operation updates P and Q segments, given a modified data segment x_a .

Sub 34
As with the Classification 2 group, the first two parameters of each Classification 3 subset indicate whether the coefficients of the group are applicable to P calculations or to Q calculations. Each of these coefficients is set to either "0" or "1". A value of "1" for the first of these coefficients indicates that the subset coefficients apply to parity segment P . A value of "1" for the second of these coefficients indicates that the subset coefficients apply to involves parity segment

Q

Each subset contains a single remaining coefficient, corresponding to the data segment x_a that is being modified:

$$P: \quad \{1, 0, p_a\} \text{ and}$$

$$Q: \quad \{0, 1, q_a\}$$

The third classification group 34 includes N pairs of such subsets, corresponding to all values of a from 0 through $N-1$. Note that these subsets correspond to a special case of the Classification 2 coefficient subsets, in which $a = b$, and can therefore be used when adding a single new data segment to a stripe.

Structure of Classification 4 Coefficient Subsets

The coefficient subsets in the fourth classification group 35 are used to reconstruct a single data segment x_a based on one of the parity segments and the surviving data segments. The coefficients correspond closely to the Classification 1 coefficients, except that they are transformed according to the mathematics $f(\)$ of the chosen error correction code to perform a reconstruction operation:

$$P: \quad \{ f(p_0, p_a), f(p_1, p_a), \dots, f(p_a), \dots, f(p_{N-1}, p_a) \}$$

$$Q: \quad \{ f(q_0, q_a), f(q_1, q_a), \dots, f(q_a), \dots, f(q_{N-1}, q_a) \}$$

More specifically:

$$P: \quad (p, q_b + p_b q_a)^{-1} ((q_b p_0 + p_b q_0), (q_0 p_1 + p_0 q_1), \dots, q_b P, \dots, (q_b p_k + p_b q_k), (q_b p_{k-1} + p_b q_{k+1}), \dots, p_b Q + \dots + (q_b p_{N-1} + p_b q_{N-1}))$$

$$P: \quad (p_a q_b + p_b q_a)^{-1} ((q_a p_0 + p_a q_0), (q_a p_1 + p_a q_1), \dots, q_a P + \dots + (q_a p_k + p_a q_k), (q_a p_{k-1} + p_a q_{k+1}), \dots, p_a Q, \dots, (q_a p_{N-1} + p_a q_{N-1}))$$


The fourth classification group includes N pairs of such subsets, corresponding to all values of a from 0 through $N-1$. Note that in each subset, the coefficient $f(p_a)$ or $f(q_a)$ corresponds to data segment x_a .

Structure of Classification 5 Coefficient Subsets

The coefficient subsets in the fifth classification group 36 are used to reconstruct two data segments x_a and x_b based on the two parity segments and the surviving data segments. The coefficients correspond closely to the Classification 1 coefficients, except that they are transformed according to the mathematics ($f()$) of the chosen error correction code to perform a reconstruction operation:

$$x_a: \{ f(p_0, q_0, p_a, p_b, q_a, q_b), f(p_1, q_1, p_a, p_b, q_a, q_b), \dots, f(p_a, p_b, q_a, q_b), \dots, f(p_k, q_k, p_a, p_b, q_a, q_b), f(p_{k+1}, q_{k+1}, p_a, p_b, q_a, q_b), \dots, f(p_a, p_0, q_a, q_b), \dots, f(p_{N-1}, q_{N-1}, p_a, p_b, q_a, q_b) \}$$

$$x_b: \{ f(p_0, q_0, p_a, p_b, q_a, q_b), f(p_1, q_1, p_a, p_b, q_a, q_b), \dots, f(p_a, p_b, q_a, q_b), \dots, f(p_k, q_k, p_a, p_b, q_a, q_b), f(p_{k+1}, q_{k+1}, p_a, p_b, q_a, q_b), \dots, f(p_a, p_0, q_a, q_b), \dots, f(p_{N-1}, q_{N-1}, p_a, p_b, q_a, q_b) \}$$

 The fifth section of the array includes $(N*(N-1))/2$ pairs of such subsets, corresponding every possible combination of a and b within the range of 0 to $N-1$. Note that in each subset, the coefficient $f(p_a, p_b, q_a, q_b)$ corresponds to data segment x_a or x_b , depending on which data segment is being reconstructed.

One possible implementation of these equations is as follows:

$$x_a: (p_a, q_b + p_b, q_a)^{-1}(q_b, p_0 + p_b, q_0), (p_a, q_b + p_b, q_a)^{-1}(q_b, p_1 + p_b, q_1), \dots, (p_a, q_b + p_b, q_a)^{-1}q_b, \dots, (p_a, q_b + p_b, q_a)^{-1}(q_0, p_k + p_0, q_k), (p_a, q_b + p_b, q_a)^{-1}(q_0, p_{k+1} + p_0, q_{k+1}), \dots, (p_a, q_b + p_b, q_a)^{-1}p_b, \dots, (p_a, q_b + p_b, q_a)^{-1}(q_0, p_{N-1} + p_0, q_{N-1})$$

$$x_b: (p_a, q_b + p_b, q_a)^{-1}(q_b, p_0 + p_b, q_0), (p_a, q_b + p_b, q_a)^{-1}(q_a, p_1 + p_a, q_1), \dots, (p_a, q_b + p_b, q_a)^{-1}q_a, \dots, (p_a, q_b + p_b, q_a)^{-1}(q_a, p_k + p_a, q_k), (p_a, q_b + p_b, q_a)^{-1}(q_a, p_{k+1} + p_a, q_{k+1}), \dots, (p_a, q_b + p_b, q_a)^{-1}p_a, \dots, (p_a, q_b + p_b, q_a)^{-1}(q_a, p_{N-1} + p_a, q_{N-1})$$

$$p_b, q_a)^{-1}(q_a, p_{k+1} + p_a, q_{k+1}), \dots, (p_a, q_b + p_b, q_a)^{-1}p_a, \dots, (p_a, q_b + p_b, q_a)^{-1}(q_a, p_{N-1} + p_a, q_{N-1})$$

Coefficient Subset Usage

Fig. 4 illustrates a method of performing parity operations in accordance with the array storage scheme described above. A first step 100 comprises classifying different parity operations into classifications that include parity segment generation operations, parity segment regeneration operations, and data segment reconstruction operations. More specifically, an operation is classified as either a parity generation operation, a parity regeneration operation resulting from added segments, a parity regeneration operation resulting from segment modification, a single data segment reconstruction operation or a double data segment reconstruction operation. Each classification of parity operations includes a plurality of different classification scenarios, each of which involves a respective subset of parity coefficients.

A step 102 comprises pre-calculating individual parity coefficients and pre-selecting subsets of parity coefficients for use in the different parity operations and the different scenarios of parity operations. This step is performed in accordance with the description already given.

A step 104 comprises storing all of the pre-selected parity coefficient subsets in an indexed linear memory array, where they can be accessed by parity computation logic. This step includes pre-formatting the coefficient subsets so that they can be efficiently utilized by hardware-based parity operation logic. In particular, the individual coefficients of each subset are packed in adjacent bytes or storage units and ordered in a way that is particular to the hardware-based parity

1 operation logic. As a result of this step, the memory array contains a single
2 coefficient subset corresponding to each different computation scenario.

3 The individual coefficients and the subsets of coefficients are packed with
4 no intervening data elements. The subsets of the array are grouped and ordered as
5 already described, with the coefficient subsets grouped into classification groups
6 by order of their classifications. Within the second classification group, the
7 subsets have varying sizes. In addition, the subsets in the second classification
8 group are sub-grouped by size, and ordered in ascending order according to their
9 lowest-numbered coefficient.

10 During parity operations, parity operation logic accesses the memory array
11 to obtain the appropriate coefficient subsets for use in the different scenarios of
12 parity operations. Thus, a step 106 comprises determining which of the stored
13 subsets of parity coefficients is needed for a particular parity operation. This step
14 involves determining the classification of the parity operation and a group offset
15 into the linear memory array, indicating the beginning of the classification group
16 corresponding to that parity operation classification. A subset offset is then
17 calculated into the group, to the location of the desired coefficient subset.

18 Step 106 is straightforward except with regard to the second classification
19 group. As described in detail above, the second classification group contains
20 coefficient subsets of varying lengths or sizes, making it difficult to determine the
21 offset of a particular coefficient subset. However, the inventors have discovered
22 that when the second classification group is arranged as described, having ordered
23 subgroups of same-sized coefficient subsets, an offset to a particular subgroup can
24 be calculated as a function of the size of the coefficient subsets of the sub-group
25 and of N (the largest number of coefficients contained by any sub-group).

Specifically, the offset to a particular sub-group i corresponding to subset size L_i is equal to :

$$((L_i - 1)(12N + L_i(3N - 2L_i - 5))/6) - 3(N - 1).$$

This formula assumes the presence in each subset of the prepended pair of constants (described above) corresponding to P and Q. L_i , however, equals $b - a$. Within the sub-group i , the offset of a particular coefficient subset is equal to $a(L_i + 2)$. Thus, the overall offset into the classification group, for a range of coefficients corresponding to x_a through x_b , is :

$$(((L_i - 1)(12N + L_i(3N - 2L_i - 5))/6) - 3(N - 1)) + a(L_i + 2).$$

The size of the second classification group is given by the following equation:

$$((N - 1)(12N + N(3N - 2N - 5))/6) - 3(N - 1).$$

After determining the appropriate offset into the memory array, a step 108 is performed of reading the determined parity coefficient subset from memory. Step 110 comprises performing the particular parity operation with the subset of parity coefficients read from memory.

Disk Controller Operation

Fig. 5 illustrates the most pertinent components of a disk controller 200 in accordance with the invention. The disk controller includes a microprocessor 201 and associated memory 202. In addition, the disk controller has a hard disk interface component 203 and a communications component 204. The hard disk interface component provides a means of access to the hard disks associated with and controlled by the disk controller. The communications component acts as an interface between a host computer and the hard disk controller.

1 In addition to these components, hard disk controller 200 includes
2 hardware-based parity operation logic 205 in the form of an application-specific
3 integrated circuit (ASIC). The term "hardware-based" is intended to mean that
4 this logic component, as opposed to software-based logic, does not retrieve and
5 execute instructions from program memory. Rather, the logic component has
6 dedicated, interconnected logic elements that process signals and data. Although
7 hardware-based logic such as this is less flexible than a microprocessor or other
8 instruction-based processors, hardware-based logic is often much faster than
9 instruction-based logic.

10 In general, the disk controller operates as follows. Microprocessor 201
11 handles communications with the host computer and coordinates all data transfers
12 to and from the host controller. In addition, the microprocessor coordinates all
13 actual disk transfers. However, data is buffered in memory 202 prior to writing to
14 disk. Parity operations are performed on data in memory 202 under the control of
15 microprocessor 201.

16 During initialization, microprocessor 201 constructs a coefficient subset
17 table 212 in memory 202. Subsequently, when it is time for a parity operation,
18 microprocessor 201 determines the classification and scenario of the parity
19 operation. Once this information is determined, the microprocessor creates a
20 script that indicates the locations in memory 202 of one or more data segments and
21 parity segments (referred to collectively as data blocks 214) that will be the object
22 of the parity operation. The script indicates an offset into the coefficient subset
23 table 212 at which the proper coefficient subset will be found for the parity
24 operation, and the number of coefficients that are contained in the coefficient
25 subset. The script also indicates the location in memory 202 at which the result of

1 the requested calculation is to be placed. Each script stores information for a
2 single parity operation and the memory structure for storing such scripts is referred
3 to herein as a task description block (TDB). The TDB is stored in a particular
4 location in memory 202 and a pointer to that location (e.g., a 32-bit address) is
5 stored in a TDB queue 216 in memory 202. A response queue 218 is also stored in
6 memory 202 and used by hardware logic 205 to return an indication to
7 microprocessor 201 as to whether a parity operation was successful.

8 When a script is placed in memory, the hardware logic is notified by the
9 presence of the pointer to the TDB for the script in queue 216. The hardware logic
10 responds by (a) retrieving the designated coefficients, data segments, and parity
11 segments, (b) performing the appropriate parity operation based on the designated
12 coefficients, (c) returning the data and/or calculated parity segments to memory,
13 and (d) indicating to microprocessor 201 whether the operation has been
14 successfully completed by writing an entry into response queue 218.

15 The hardware logic is configured to perform the various different parity
16 operations by summing products of coefficients and data/parity segments. The
17 different operations actually vary only in the number and choice of coefficients,
18 data segments, and parity segments. These variables are specified by the script.
19 Thus, the operations lend themselves very conveniently to hardware-based
20 calculations.

21 *Sally*
Ale A simultaneously filed and co-pending U.S. Patent Application attorney
22 docket no. 10001494, entitled "Using Task Description Blocks To Maintain
23 Information Regarding Operations", to inventors Barry J. Oldfield and Robert A.
24 Rust, describes TDBs and their use, and is hereby incorporated by reference.
25

Sub
97

1 Other simultaneously filed and co-pending U.S. Applications describe
2 technologies useful in conjunction with the invention, including U.S. Patent
3 Application attorney docket no. 10001489, entitled "Methods And Arrangements
4 For Improved Strip-Based Processing, to inventors Barry J. Oldfield and Robert
5 A. Rust; U.S. Patent Application attorney docket no. 10001493, entitled "Memory
6 Manager for a Common Memory, to inventors Barry J. Oldfield and Robert A.
7 Rust; and U.S. Patent Application attorney docket no. 10001491, entitled
8 "Efficient Parity Operations," to inventors Michael B. Jacobson, Barry J. Oldfield
9 and Robert A. Rust;. These applications are hereby incorporated by reference.
10

11 **Conclusion**

12 The parity calculation architecture described above has a number of
13 advantages over the prior art. One significant advantage is that the architecture
14 allows parity computations to be performed by hardware-based logic, without
15 requiring significant complexity in the hardware. To provide this advantage, a
16 microprocessor performs preliminary work such as designating the various
17 parameters to be used in the calculations. Once the proper coefficients and
18 data/parity segments have been designated, the hardware can perform the actual
19 calculations in similar or identical ways, regardless of the particular type of
20 operation that is requested.

21 The pre-selection of coefficient subsets, and their arrangement in memory,
22 provides further efficiencies by eliminating many steps that would otherwise be
23 required to select coefficients prior to every parity operation. Furthermore, the
24 unique indexing method, particular with regard to the described second section of
25

1 the array, allows the coefficients to be packed in memory to save space, even
2 though the coefficient subsets have differing lengths.

3 Although the invention has been described in language specific to structural
4 features and/or methodological steps, it is to be understood that the invention
5 defined in the appended claims is not necessarily limited to the specific features or
6 steps described. Rather, the specific features and steps are disclosed as preferred
7 forms of implementing the claimed invention.